


## PNP Silicon Epitaxial Planar Transistor

The transistor is subdivided into three groups Q, R and S according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.



1.Base 2.Emitter 3.Collector  
SOT-23 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$-V_{CBO}$	60	V
Collector Current	$-I_C$	150	mA
Power Dissipation	$P_{tot}$	200	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_s$	-55 to +150	$^\circ\text{C}$

### Characteristics at $T_{amb}=25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit	
DC Current Gain at $-V_{CE}=6\text{V}$ , $-I_C=1\text{mA}$	Q	$h_{FE}$	120	270	-
	R	$h_{FE}$	180	390	-
	S	$h_{FE}$	270	560	-
Collector Cutoff Current at $-V_{CB}=60\text{V}$	$-I_{CBO}$	-	0.1	$\mu\text{A}$	
Emitter Cutoff Current at $-V_{EB}=6\text{V}$	$-I_{EBO}$	-	0.1	$\mu\text{A}$	
Collector Saturation Voltage at $-I_C=50\text{mA}$ , $-I_B=5\text{mA}$	$-V_{CE(sat)}$	-	0.5	V	
Collector Base Breakdown Voltage at $-I_C=50\mu\text{A}$	$-V_{(BR)CBO}$	60	-	V	
Collector Emitter Breakdown Voltage at $-I_C=1\text{mA}$	$-V_{(BR)CEO}$	50	-	V	
Emitter Base Breakdown Voltage at $-I_E=50\mu\text{A}$	$-V_{(BR)EBO}$	6	-	V	
Transition Frequency at $-V_{CE}=12\text{V}$ , $-I_C=2\text{mA}$ , $f=30\text{MHz}$	$f_T$	120	-	MHz	