

## Silicon Epitaxial Planar Diode

Low leakage switching diode


### Features

- Plastic SMD package
- Low leakage current

### Application

- Low leakage current applications in surface mounted circuits.

### MARKING: JV



### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )


Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	85	V
Continuous Reverse Voltage	$V_R$	75	V
Continuous Forward Current	$I_F$	200	mA
Repetitive Peak Forward Current	$I_{FRM}$	500	mA
Non-Repetitive Peak Forward Surge Current	$I_{FSM}$	$t = 1\ \mu\text{s}$	4
		$t = 1\ \text{ms}$	1
		$t = 1\ \text{s}$	0.5
Power Dissipation	$P_{tot}$	200	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 65 to + 150	$^\circ\text{C}$

### Characteristics at $T_a = 25\text{ }^\circ\text{C}$


Parameter	Symbol	Typ.	Max.	Unit
Forward Voltage	$V_F$	-	at $I_F = 1\ \text{mA}$	0.9
			at $I_F = 10\ \text{mA}$	1
			at $I_F = 50\ \text{mA}$	1.1
			at $I_F = 150\ \text{mA}$	1.25
Reverse Current	$I_R$	-	at $V_R = 75\ \text{V}$	5
			at $V_R = 75\ \text{V}, T_j = 150\text{ }^\circ\text{C}$	80
Diode Capacitance	$C_d$	2	-	pF
Reverse Recovery Time	$t_{rr}$	-	3	$\mu\text{s}$
at $I_F = I_R = 10\ \text{mA}, R_L = 100\ \Omega, i_{rr} = 0.1\ I_R$				

## Typical Characteristics


**Forward Characteristics**



**Reverse Characteristics**



**Capacitance Characteristics**



**Power Derating Curve**

