


**Features**

- Glass Passivated Die Construction
- Ideally Suited for Automatic Assembly
- Low Forward Voltage Drop, High Efficiency
- Low Power Loss
- Super-Fast Recovery Time
- Plastic Case Material has UL Flammability Classification Rating 94V-O

**Mechanical Data**






- Case: SMBF , Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.0018 ounces, 0.05grams


**Maximum Ratings and Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	ES3AF	ES3BF	ES3CF	ES3DF	ES3EF	ES3GF	ES3JF	Unit	
Peak Repetitive Reverse Voltage	$V_{RRM}$									
Working Peak Reverse Voltage	$V_{RWM}$	50	100	150	200	300	400	600	V	
DC Blocking Voltage	$V_R$									
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	105	140	210	280	420	V	
Average Rectified Output Current @ $T_L = 75^\circ\text{C}$	$I_O$	3.0								A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	100								A
Forward Voltage @ $I_F = 3.0\text{A}$	$V_{FM}$	0.95				1.25		1.7	V	
Peak Reverse Current @ $T_A = 25^\circ\text{C}$ At Rated DC Blocking Voltage @ $T_A = 100^\circ\text{C}$	$I_{RM}$	5.0 500								$\mu\text{A}$
Reverse Recovery Time (Note 1)	$t_{rr}$	35								nS
Typical Junction Capacitance (Note 2)	$C_j$	45								pF
Typical Thermal Resistance (Note 3)	$R_{\theta JL}$	16								$^\circ\text{C/W}$
Operating and Storage Temperature Range	$T_j, T_{STG}$	-65 to +150								$^\circ\text{C}$

Note: 1. Measured with  $I_F = 0.5\text{A}$ ,  $I_R = 1.0\text{A}$ ,  $I_{rr} = 0.25\text{A}$ . See figure 5.  
 2. Measured at 1.0 MHz and applied reverse voltage of 4.0 V DC.  
 3. Mounted on P.C. Board with 8.0mm<sup>2</sup> land area.

**RATINGS AND CHARACTERISTIC CURVES ES3AF THRU ES3JF**
**AVERAGE FORWARD RECTIFIED CURRENT,  
AMPERES**
**FIG. 1- FORWARD CURRENT DERATING CURVE**

**PEAK FORWARD SURGE CURRENT,  
AMPERES**
**FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**

**INSTANTANEOUS FORWARD CURRENT,AMPERES**
**FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**

**INSTANTANEOUS REVERSE CURRENT,  
MICROAMPERES**
**FIG. 4-TYPICAL REVERSE CHARACTERISTICS**

**JUNCTION CAPACITANCE, pF**
**FIG. 5-TYPICAL JUNCTION CAPACITANCE**

**TRANSIENT THERMAL IMPEDANCE,  
°C/W**
**FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE**
