

FEATURES

- For surface mounted applications
- Low profile package
- Built-in strain relief
- Easy pick and place
- Ultrafast recovery times for high efficiency
- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- Glass passivated junction
- High temperature soldering: 260 °C/10 seconds at terminals

MECHANICAL DATA

Case: JEDEC DO-214AC, molded plastic


Terminals: Solderable per

MIL-STD-202, Method 208

Polarity: Color band denotes cathode

Weight: 0.003 ounces, 0.093 grams

Mounting position: Any


MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.






Resistive or inductive load.

For capacitive load, derate current by 20%.

	SYMBOLS	UF1A	UF1B	UF1D	UF1G	UF1J	UF1K	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	Volts
Maximum Average Forward Rectified Current, at $T_L=100\text{ }^\circ\text{C}$	$I_{(AV)}$	1.0						Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load(JEDEC method) $T_A=55\text{ }^\circ\text{C}$	I_{FSM}	30.0						Amps
Maximum Instantaneous Forward Voltage at 1.0A	V_F	1.0		1.4		1.7		Volts
Maximum DC Reverse Current $T_A=25\text{ }^\circ\text{C}$ At Rated DC Blocking Voltage $T_A=100\text{ }^\circ\text{C}$	I_R	10.0 100						$\mu\text{ A}$
Maximum Reverse Recovery Time (Note 1) $T_J=25\text{ }^\circ\text{C}$	T_{RR}	50.0				100.0		ns
Typical Junction capacitance (Note 2)	C_J	17.0						pF
Maximum Thermal Resistance (Note 3)	$R_{\theta JL}$	30						$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_{STG}	-50 to +150						$^\circ\text{C}$

NOTES:

1. Reverse Recovery Test Conditions: $I_F=0.5\text{ A}$, $I_R=1.0\text{ A}$, $I_{rr}=0.25\text{ A}$
2. Measured at 1 MHz and Applied reverse voltage of 4.0 volts
3. 8.0 mm^2 (.013mm thick) land areas


Fig. 1-REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM

Fig. 2-FORWARD CHARACTERISTICS

Fig. 3- TYPICAL JUNCTION CAPACITANCE

Fig. 4- FORWARD CURRENT DERATING CURVE

Fig. 5-PEAK FORWARD SURGE CURRENT